LA-UR-14-20877

Approved for public release; distribution is unlimited.

Title: Modular Pumped Hydro for Grid Energy Storage

Author(s): Bibeault, Mark L.

Intended for: Slide presentation for program development activities.

Issued: 2014-02-12



Disclaimer:

Disclaimer:
Los Alamos National Laboratory, an affirmative action/equal opportunity employer,is operated by the Los Alamos National
Security, LLC for the National NuclearSecurity Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396.
By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.
Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Departmentof Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Modular Pumped Hydro for Grid Energy Storage

Mark L. Bibeault, AET-1

bibeault@lanl.gov

AET Summer Student Seminar Series June 26, 2013

LAUR-13-xxxx



UNCLASSIFIED

Why Energy Storage? Best Utilize Our Water and Fuel Resources.






Figure I-1 of "Energy Demands on Water Resources, A Report to Congress", US DOE, December 2006.

UNCLASSIFIED

The Holes That We Dig and Must Fill. (It's Mind Boggling!)

 OIL: 85 million barrels/day • OIL: $1.1 \times 1.1 \times 1.1$ cubic miles per year


- NATURAL GAS: 260 billion cubic feet/day
- As liquid: $1.3 \times 1.3 \times 1.3$ cubic miles per year
- Coal: 14 million tons/day
- COAL: $1.0 \times 1.0 \times 1.0$ cubic miles per year

Slide 16 of presentation "Will There be Enough Energy for All in the 21'st Century", LA-UR-06-2989, 2006, by Rajan Gupta.



Total US Fuel(Electric Gen) and Water Usage (More Mind Boggling)

% Net US Fuel Consumption (2009) Electric Generation



US Energy Information Administration/Electric Power Monthly, March 2010, Table ES1.B for 2009, for all sectors.


U.S. Freshwater Withdrawals, 345 Bgal/day Public Supply, 13% Industrial, 5% Mining, 1% Thermoelectric, Irrigation, 40% 39%

Figure II-1 of "Energy Demands on Water Resources, A Report to Congress", US DOE, December 2006.





How Does Energy Storage Fit In? Variable/Uncertain Generation Increased Need for Grid Flexibility




Reproduced from material developed by Anthony Price, Regenesys Ltd.

Adapted From Figure on pg. 7 "Load Profile for a Large Scale Energy Storage Facility," from "Energy Storage—The Missing Link in the Electricity Value Chain, An Energy Storage Council White Paper," copyright May, 2002.



How Does Energy Storage Fit In? Variable/Uncertain Generation Increased Need for Grid Flexibility



Reproduced from material developed by Anthony Price, Regenesys Ltd.


Adapted From Figure on pg. 7 "Load Profile for a Large Scale Energy Storage Facility," from "Energy Storage—The Missing Link in the Electricity Value Chain, An Energy Storage Council White Paper," copyright May, 2002.



To Be Fair.....

There are other ways to provide grid flexibility

(It's All About Economics and Risk!)






Paul Denholm et. el, "The Role of Energy Storage with Renewable Electricity Generation", Fig 4.10, Technical Report NREL/TP-6A2-47187, January 2010.


UNCLASSIFIED

We'll Continue with Energy Storage






Slide 15 from presentation by Aiden Tuohy and Dan Rastler of Electric Power Research Institute, "Wind Integration And Energy Storage", MISO Energy Storage Workshop, June 29, 2011.



Slide 15 from presentation by Aiden Tuohy and Dan Rastler of Electric Power Research Institute, "Wind Integration And Energy Storage", MISO Energy Storage Workshop, June 29, 2011.

Today, Energy Storage Penetration is Actually Very Small

Worldwide installed storage capacity for electrical energy




Slide 20 from presentation by Aiden Tuohy and Dan Rastler of Electric Power Research Institute, "Wind Integration And Energy Storage", MISO Energy Storage Workshop, June 29, 2011.



Growth in Pumped Hydro Faces Challenges








Design of Modular Pumped Hydro (MPH) 80% Efficient (Full cycle)

- Up 1 GW-hr electric storage
- Closed-loop pumped hydro technology
- "Smart sited" near existing renewable production & transmission lines, away from endangered species, environmentally sensitive areas
- Permit/Build/Commission < 4 yr</p>
- < 20 acres reservoirs</p>
- 1.1 \$/W = Total Cost
- Produce no emissions or solid waste
- Zero net water consumption

Produced Energy = (efficiency) (density) g (head) (volume)






UNCLASSIFIED



Modular Pumped Hydro(MPH) Details


Design

- Ring embankment, earth fill
- Cover & line
- Leakage recycled
- Catch rainfall
- Complimentary solar siting
- 30 to 300 m head
- 30 to 300 MW power rating
- < 12 hrs discharge</p>
- Each reservoir
 - 1000 acre-ft volume
 - 10 acres surface area
 - Locate flat top mtn. w/flat basin





Behind the Scenes Work






UNCLASSIFIED

View of Reversible Francis Turbine/Pump

One of 6 turbines for Grand Coulee Dam project, Columbia River, State of Washington, each rated at 750 MW, from the Bureau of Reclamation via Wikipedia.





From Fig 1.3 of Thesis for Doctor of Philosophy, "Numerical Investigations of Turbulent Flow in Water Turbines", Hakan Nilsson, Department of Thermo and Fluid Dynamics, Chalmers University of Technology, Goteborg, Sweden, 2002. Picture courtesy of GE Energy (Sweden) AB.

Los Alamos NATIONAL LABORATORY

UNCLASSIFIED Slide 15

Program Development

- Lots of meetings
 - Tech Transfer
 - Energy Council
 - Program Managers
- Mentor Program
- Oak Ridge National Laboratory
- Discussions with Utilities
 - Jemez Electric/Tri-State
- Discovery Day





Modular Pumped Hydro (MPH) Example Case/Cost Study for Discovery Day

- Location: 200 MW NM Wind Center, Vaughn, NM
- Store energy 18 hrs per day, release to grid 6 hrs per day (during peak demand)
- 25% Wind Farm operational cycle
- H = 400 ft (122 m), Reservoir Volume = 1639 acre-ft
- **Energy Storage Power = 150 MW**
- Total energy released = 219 MW-hrs*

Table 1 : Financial Results (Total = 153.1 \$M)

Item	Result
Normalized Cost (\$/W)	1.02
Normalized Profit (\$/MW-hr)	48.63
Yearly Profit (\$M)*	10.83
Total Cost (\$M)	153.1
Interest (%)	4.00
Monthly Payment (\$M)	0.9024
Payback (yrs)	20.87

^{*}for energy storage facility





Comparison of Gas Turbine and MPH (150 MW)

Parameter	Gas Turbine	МРН
Capital Cost (\$/W)	0.7	1.03
Operating Cost(mills/kW-hr)	0.045	0.01
Total Capital(\$M)	105	153.1
20 Year Operational Cost	197.1	43.8
Total Cost (\$M)	302.1	196.9
Net Efficiency (%)	40	80
Fuel Costs	Variable	Stable
Ancillary Services	Some	Full
Net Water Usage	Yes	None
Startup to Full Power (no warm standby)	< 30 min	< 60 sec



Where Do We Go From Here? A Work In Progress....

- Collaboration with NMSU
- Non Disclosure Agreements
- **Preliminary Site Selection**
- **Verify Financials**
- Perform A Feasibility Study
 - 1 year+ at \$1.5 -- 2M
 - Includes Utilities, State Universities, Contractors
 - Team members:
 - Geotechnical Engineering
 - Pumped Hydro
 - Electrical Engineering
 - **Grid Modeling**
 - **Engineering Economics**
 - Systems Engineering & Logistics
 - Permitting Policy & Regulation

